


PIN OUT		
P1	—————	P2
1	—————	8
2	—————	3
3	—————	2
4	—————	20
5	—————	7
6	—————	6
7	—————	4
8	—————	5
9	—————	22
SHELL	—————	SHELL

NOTE:

1. WIRE: 26AWG, UL1061 + CSA.
2. CONNECTOR: P1: D-SUB 9PIN FEMALE, SOLDER TYPE, GOLD FLASH CONTACTS.
P2: D-SUB 25PIN MALE, SOLDER TYPE, GOLD FLASH CONTACTS.

3. THUMB SCREW TO BE MOLDED.
4. SHIELDING: AL-FOIL TAPE COVER PREMOLD AND 100% CONTACT WITH SHELL.
5. HOOD: MOLDED BEIGE(CTG-401) PVC.
6. PACKING: 4PCS HEX. NUTS (5 X 5.5mm, #4-40 UNC) IN A PE POLY-BAG, SEALED, HEX. NUTS AND AN ADAPTER IN A CLEAR ZIP-LOCK POLY-BAG TOGETHER. BAR CODE LABEL(ORANGE BACKGROUND WITH BLACK LETTERS, CODE: 39) TO BE STAMPED ON POLY-BAG TO READ:

Molded Type Adapter
DB25 Male to DB9 Female



A12-25M-9F
TRI-NET TECHNOLOGY INC.



- O
- S

DRAWING APPROVED _____		DATE: _____	
SAMPLE APPROVED PER _____		DRAWING SPECIFICATIONS _____	
PROPRIETARY & CONFIDENTIAL. THIS DOCUMENT MAY NOT BE COPIED, OR DISCLOSED IN WHOLE OR IN PART WITHOUT THE WRITTEN CONSENT OF TNT.			
	mm	TITLE	DB9 FEMALE TO DB25 MALE
SCALE	NONE	CUS. NAME	
SHEET	1/1	CUS. P/N	A12-25M-9F
DIMENSIONAL TOLERANCES UNLESS OTHERWISE NOTED		PART NO.	P9907041-E
.X ±	0.2	ENG.	DATE
.XXX ±	ANGLES ±	CHECKED	DATE
REV. ∅	CUS. REV A	APPROVED	DATE

