


PIN OUT	
P1	P2
1	8
2	3
3	2
4	20
5	7
6	6
7	4
8	5
9	22
SHELL	SHELL

NOTE:

1. WIRE: 26AWG, UL1061 + CSA.
2. CONNECTOR: P1: D-SUB 9PIN MALE, SOLDER TYPE, GOLD FLASH CONTACTS.  
P2: D-SUB 25PIN MALE, SOLDER TYPE, GOLD FLASH CONTACTS.
3. THUMB SCREW TO BE MOLDED.
4. SHIELDING: AL-FOIL TAPE COVER PREMOLD AND 100% CONTACT WITH SHELL.
5. HOOD: MOLDED BEIGE(CTG-401) PVC.
6. PACKING: 4PCS HEX. NUTS (5 X 5.5mm, #4-40 UNC) IN A PE POLY-BAG SEALED, HEX. NUTS AND AN ADAPTER IN A CLEAR ZIP-LOCK POLY-BAG TOGETHER. BAR CODE LABEL(BLUE BACKGROUND WITH BLACK LETTERS, CODE 39) TO BE STAMPED ON POLY-BAG TO READ:

Molded Type Adapter  
DB25 Male to DB9 Male



A12-25M-9M  
TRI-NET TECHNOLOGY INC.



O

S

DRAWING APPROVED _____		DATE: _____	
SAMPLE APPROVED PER _____		DRAWING SPECIFICATIONS _____	
PROPRIETARY & CONFIDENTIAL. THIS DOCUMENT MAY NOT BE COPIED, OR DISCLOSED IN WHOLE OR IN PART WITHOUT THE WRITTEN CONSENT OF TNT.			
	mm	TITLE DB9 MALE TO DB25 MALE	
SCALE	NONE	CUS. NAME	
SHEET	1/1	CUS. P/N A12-25M-9M	
DIMENSIONAL TOLERANCES UNLESS OTHERWISE NOTED		PART NO. P9907042-E	
.X ±	0.2	.XX ±	
.XXX ±		ANGLES ±	
REV.	∅	CUS. REV	A
		ENG.	DATE
		CHECKED	DATE
		APPROVED	DATE

