



接线表

P1	P2	P1	P2
1	1	14	14
2	2	15	32
3	3	16	31
4	4	17	36
5	5	18	33
6	6	19	19
7	7	20	21
8	8	21	23
9	9	22	25
10	10	23	27
11	11	24	29
12	12	25	30
13	13	铁壳	铁壳

注:

1. 电子线: 26H, UL1061.

2. 插头: P1: DB25F: 焊, 黑.

P2: CN36M: 焊, 蓝, 传统型.

③ DB25/CN36转换电镀装配壳(银色, 自扣型).

④ 螺丝: (P/N: 300101510001).

⑤ 六角螺母(P/N: 3021006011), 可活动.

6. 包装: 依CTG包装规范: CTG-PK-2. (每PC
装4"X5.5"X0.06mmCTG印刷由任袋)

标签: 白底黑字, 10X80mm. 贴于CTG印刷由任袋上.

DGC25F36M
DB25F TO 36 CENT M GENDER CHANGER

条码标签(#02755)贴于CTG印刷由任袋上(详见CTG-BAR-PK).



PROPRIETARY & CONFIDENTIAL. THIS DOCUMENT MAY NOT BE COPIED OR DISCLOSED IN WHOLE OR IN PART WITHOUT THE WRITTEN CONSENT OF CTC INTERNATIONAL LTD.

REV	DATE	DESCRIPTION	 Tri-Net Technology / U.S.A. 张剑平 09/10 09/10 09/10
SCALE	NAME	TASK DB25F/CN36M GENDER CHANGER D.W. PYS (CTC) DGC25F36M	
SHEET	1/1	P/N A13-25F-36M BRW NO. P9808064	
CHANGER, PRELIMINARY	DATE		