



FEMALE BAILLOCK HARDWARE

PIN OUT

P1	—	P2	P1	—	P2
1	—	1	14	—	14
2	—	2	15	—	32
3	—	3	16	—	31
4	—	4	17	—	36
5	—	5	18	—	33
6	—	6	19	—	19
7	—	7	20	—	21
8	—	8	21	—	23
9	—	9	22	—	25
10	—	10	23	—	27
11	—	11	24	—	29
12	—	12	25	—	30
13	—	13	SHELL	—	SHELL

NOTE:

1. WIRE: 26AWG, UL1061.
2. CONNECTOR: P1: D-SUB 25PIN MALE, SOLDER TYPE, GOLD FLASH CONTACTS.
P2: CENTRONICS 36PIN FEMALE, SOLDER TYPE, GOLD FLASH CONTACTS.
3. METAL SCREW.
4. CONNECTORS ARE MOUNTED IN A METALIZED PLASTIC HOOD. (PLATED CHROME)
5. PACKING: EACH ADAPTER IN A CLEAR ZIP-LOCK POLY-BAG. LABEL (WHITE BACKGROUND WITH BLACK LETTERS) TO BE STAMPED ON CLEAR ZIP-LOCK POLY-BAG TO READ.

DGC25M36F
DB25M TO 36 CENT F GENDER CHANGER



DRAWING APPROVED		DATE:	
SAMPLE APPROVED PER DRAWING SPECIFICATIONS		DATE:	
<small>PROPRIETARY & CONFIDENTIAL. THIS DOCUMENT MAY NOT BE COPIED, OR DISCLOSED IN WHOLE OR IN PART WITHOUT THE WRITTEN CONSENT OF CTG INTERNATIONAL LTD.</small>			
<input type="checkbox"/> D	ITEM	FILE	DB25M/ON36F
<input type="checkbox"/> I	SCALE	GENDER CHANGER	
<input type="checkbox"/> Q	SHEET	1/1	CTG
<input type="checkbox"/> S	QUANTITY	A13-25M-36F	Tri-Net Technology / U.S.A.
	REV	P9808063-E	MAY 26/2005