



PIN OUT: 09Male

25Female

1	-----	8
2	-----	3
3	-----	2
4	-----	20
5	-----	7
6	-----	6
7	-----	4
8	-----	5
9	-----	22
G	-----	G

Label: orange color with white character

One side: SERIAL PORT ADAPTORS D9/D25

The other side: MINI ADAPTER.

SPECIFICATION

INSULATOR: PBT Glass fibre reinforced UL 94 V0

CONTACT: Brass

CONTACT PLATING: Gold plated over nickel

SHELL: Tin plated shell

CURRENT RATING: 3 AMP

DIELECTRIC STRENGTH: 500V AC for one minute

INSULATOR RESISTANCE: 500M Ω min at 500V DC

TEMPERATURE: -25° ~~~ $+105^{\circ}$.



TOLERANCE		M/M	Tri-Net Technology, Inc. http://www.trinetusa.com			
INCHES						
.X	.015	.30	SCALE	NONE	REV A	
.XX	.010	.10	UNIT	MM		
.XXX	.005	.05	SHEET	1/1		
DRAWN BY		Debird	DATE	05/06/05	DWG NO.	
CHECK BY			TITLE MA 004A (DB25F/9M ADAPTOR)			
APPD BY			PART NO. A15-D25F-9M			