


UNC #4-40 Hexscrew



DB9M/F ADAPTOR

PIN OUT: 09Male		09Female	
2	-----	3	
3	-----	2	
4	-----	1	
		6	
5	-----	5	
1	-----	4	
6	-----		
7	-----	8	
8	-----	7	
G	-----	G	

Label: orange color with white character
 One side: NULL MODEM
 The other side: MINI ADAPTER.

SPECIFICATION

INSULATOR: PBT Glass fibre reinforced UL 94 V0
 CONTACT: Brass
 CONTACT PLATING: Gold plated over nickel
 SHELL: Tin plated shell
 CURRENT RATING: 3 AMP
 DIELECTRIC STRENGTH: 500V AC for one minute
 INSULATOR RESISTANCE: 500M Ω_{min} at 500V DC
 TEMPERATURE: -25° ~ ~ +105°.



TOLERANCE		INCHES		M/M		TNT Tri-Net Technology, Inc. http://www.trinetusa.com					
.X	.015	.30	SCALE	NONE	⊕	REV	A	SHEET	1/1	DWG NO.	TNT-ADAP-0051
.XX	.010	.10	UNIT	MM							
.XXX	.005	.05	DRAWN BY	DATE	TITLE		DB9M/F ADAPTOR				
			CHECK BY	09/11/04	PART NO.		A15-D9M-9F				
			APPD BY								