


NOTE:

- 1. CABLE: 28AWG X 4C, AL-FOIL SHIELDED WITH DRAIN WIRE, NON-UL, BEIGE (CTG-401) PVC JACKET.
- 2. CONNECTOR: P1: MINI DIN 6PIN MALE: SOLDER TYPE, GOLD FLASH CONTACTS; P2: DIN 5PIN FEMALE: SOLDER TYPE, NICKEL PLATED CONTACTS.
- 3. SHIELDING: AL-FOIL TAPE COVER PREMOLD AND 100% CONTACT WITH SHELL.
- 4. ALL HOOD: MOLDED BEIGE(CTG-401) PVC.
- 5. PACKING: EACH CABLE IN A TNT PRINTED ZIP-LOCK POLY-BAG. LABEL (PINK BACKGROUND WITH BLACK LETTERS, CODE: 39) TO BE STAMPED ON POLYBAG.


PIN OUT

P1	————	P2
5	————	1
1	————	2
3	————	4
4	————	5
SHELL	————	SHELL(DRAIN WIRE)

Keyboard Accessories  
AT Female TO P/S2 Male Cable



A23-D5F-MD6M-6

DRAWING APPROVED _____		DATE: _____	
SAMPLE APPROVED PER DRAWING SPECIFICATIONS _____		DATE: _____	
PROPRIETARY & CONFIDENTIAL. THIS DOCUMENT MAY NOT BE COPIED, OR DISCLOSED IN WHOLE OR IN PART WITHOUT THE WRITTEN CONSENT OF TNT.			
	mm	TITLE	
SCALE	NONE	TITLE	
SHEET	1/1	CUS. NAME	
DIMENSIONAL TOLERANCES UNLESS OTHERWISE NOTED		CUS. P/N	ENG. _____ DATE _____
<input type="checkbox"/> 0	.X ± 0.2	.XX ±	CHECKED _____ DATE _____
<input type="checkbox"/> S	.XXX ±	ANGLES ±	APPROVED _____ DATE _____
REV.	∅	CUS. REV	A
		PART NO.	P9907036-E

