



MA 007D (DB9F/MD6F ADAPTOR)

PIN OUT: 09Female		06Female	
3	-----	3	
6	-----		
5	-----	4	
8	-----	5	
9	-----	1	
G	-----	G	

Label: orange color with white character

One side: PS2 MOUSE ADAPTORS D9/MD6

The other side: R.O.C. PATENT 105471

SPECIFICATION

INSULATOR: PBT Glass fibre reinforced UL 94 V0

CONTACT: Brass

CONTACT PLATING: Gold plated over nickel

SHELL: Tin plated shell

CURRENT RATING: 3 AMP

DIELECTRIC STRENGTH: 500V AC for one minute

INSULATOR RESISTANCE: 500MΩ min at 500V DC

TEMPERATURE: -25°C — +105°C



				Edition	Tri-Net Technology/USA				
				A0	<small>UNLESS OTHERWISE SPECIFIED TOLERANCES:</small> 0.05: ±0.20 0.00: ±0.15 0.000: ±0.05	PART NO.	DWG NO.	DATE	
				SCALE		A24-DB9F-MD6F-S	TM0069-01	05.11.00	
				UNIT					
				mm					
Customer	REVISION	DESCRIPTION	DATE	Page	1/1	DRAWN	<i>Fu Hao</i>	CHECKED	APPRD