



MA 007B (DB9F/MD6M ADAPTOR)

PIN OUT: 09Female		06Male
3	-----	3
6	-----	
5	-----	4
8	-----	5
9	-----	1
G	-----	G

Label: orange color with white character

One side: PS2 MOUSE ADAPTORS D9/MD6

The other side: R.O.C. PATEN 105471

SPECIFICATION

INSULATOR: PBT Glass fibre reinforced UL 94 V0

CONTACT: Brass

CONTACT PLATING: Gold plated over nickel

SHELL: Tin plated shell

CURRENT RATING: 3 AMP

DIELECTRIC STRENGTH: 500V AC for one minute

INSULATOR RESISTANCE: 500M Ω min at 500V DC

TEMPERATURE: -25 $^{\circ}$ C +105 $^{\circ}$ C



				Edition	A0	Tri-Net Technology/USA				
				SCALE	2:1					PART NO.
				UNIT	mm	A24-DB9F-MD6M-S		TM0067-01		05.11.00
Customer	REVISION	DESCRIPTION	DATE	Page	1/1	DRAWN	<i>Fu Hao</i>	CHECKED		APPRD

UNLESS OTHERWISE SPECIFIED TOLERANCE:
0.3 0.10 0.20
0.300 0.100 0.200

