



MA 007C (DB9M/MD6M ADAPTOR)

PIN OUT: 09Male		06Male
3	-----	3
6	-----	
5	-----	4
8	-----	5
9	-----	1
G	-----	G

Label: orange color with white character  
 One side: PS2 MOUSE ADAPTORS D9/MD6  
 The other side: R.O.C. PATENT 105471

**SPECIFICATION**

INSULATOR: PBT Glass fibre reinforced UL 94 V0  
 CONTACT: Brass  
 CONTACT PLATING: Gold plated over nickel  
 SHELL: Tin plated shell  
 CURRENT RATING: 3 AMP  
 DIELECTRIC STRENGTH: 500V AC for one minute  
 INSULATOR RESISTANCE: 500MΩ min at 500V DC  
 TEMPERATURE: -25°C — +105°C

				Edition	A0	<b>Tri-Net Technology/USA</b>			
				SCALE	2:1				
				UNIT	mm	A24-DB9M-MD6M-S	TMO068-01	05.11.00	
Customer	REVISION	DESCRIPTION	DATE	Page	1/1	DRAWN	<i>Fu Hao</i>	CHECKED	APPRD

UNLESS OTHERWISE SPECIFIED TOLERANCE:  
 0.30 0.15  
 0.30 0.20  
 0.300 0.15

