



NOTE:

1. CABLE: 28AWG X 25C, AL-FOIL SHIELDED WITH A DRAIN WIRE, UL2464, BEIGE (CTG-401) PVC JACKET.
2. CONNECTOR: P1: D-SUB 25PIN MALE: SOLDER TYPE, BLACK PBT INSULATION, GOLD FLASH CONTACTS, UL RECOGNIZED.
P2: CENTRONICS 36PIN MALE: SOLDER TYPE, GOLD FLASH CONTACTS, BLUE PBT INSULATION, UL RECOGNIZED.
3. THUMB SCREW TO BE MOLDED BEIGE (CTG-401) PVC, UL94V-0.
4. SHIELDING: AL-FOIL TAPE COVER PREMOLD AND 100% CONTACT WITH SHELL.
5. ALL HOOD: MOLDED BEIGE (CTG-401) PVC, UL94V-0.
6. TESTING: 100% ELECTRICAL TEST AT 1M OHM INSULATION RESISTANCE.
7. PACKING: EACH CABLE IN A TNT PRINTED ZIP-LOCK POLY-BAG. BAR CODE LABEL (WHITE BACKGROUND WITH BLACK LETTERS, SEE "DETAIL A", CODE: 39) TO BE STAMPED ON POLYBAG.

Parallel Printer Cable
DB25 Male to Centronics 36, xxft

C01UL-25M-36M-25**

*** & xx SEE P/N CHART
DETAIL A

CHART

P/N	**	xx	L	T
C01UL-25M-36M-2503	03	3	914	±25
C01UL-25M-36M-2506	06	6	1829	±51
C01UL-25M-36M-2510	10	10	3048	±51
C01UL-25M-36M-2515	15	15	4572	+152/-51
C01UL-25M-36M-2524	24	24	7315	+152/-51



DRAWING APPROVED _____		DATE: _____	
SAMPLE APPROVED PER DRAWING SPECIFICATIONS _____		DATE: _____	
PROPRIETARY & CONFIDENTIAL, THIS DOCUMENT MAY NOT BE COPIED, OR DISCLOSED IN WHOLE OR IN PART WITHOUT THE WRITTEN CONSENT OF TNT.			
	mm	TITLE	DB25M TO CN36M
SCALE	NONE	CUS. NAME	
SHEET	1/2	CUS. P/N	C01UL-25M-36M-25**
DIMENSIONAL TOLERANCES UNLESS OTHERWISE NOTED		DRAW NO.	P0205155-E
± 0.2	± 0.2	ENG.	<i>[Signature]</i> DATE 6/1/02
± 0.2	± 0.2	CHECKED	<i>[Signature]</i> DATE 6/1/02
REV. 0	CUS. REV.	APPROVED	<i>[Signature]</i> DATE 6/1/02