



- NOTE:
1. CABLE: 28AWG X 25C, AL-FOIL SHIELDED WITH DRAIN WIRE, NON-UL, BEIGE (CTG-401) PVC JACKET.
 2. CONNECTOR: P1: D-SUB 25PIN MALE: SOLDER TYPE, GOLD FLASH CONTACTS; P2: D-SUB 25PIN FEMALE: SOLDER TYPE, GOLD FLASH CONTACTS.
 3. THUMB SCREW TO BE MOLDED.
 4. SHIELDING: AL-FOIL TAPE COVER PREMOLD AND 100% CONTACT WITH SHELL.
 5. ALL HOOD: MOLDED BEIGE(CTG-401) PVC.
 6. PACKING: 1. 4PCS METRIC(M2.6) SCREW IN A CLEAR POLYBAG, SEALED, LABEL (WHITE BACKGROUND WITH BLACK LETTERS, SEE "DETAIL A") TO BE STAMPED ON POLYBAG.
2. EACH CABLE & PACKAGED SCREW IN A TNT PRINTED ZIP-LOCK POLY-BAG.
BAR CODE LABEL (WHITE BACKGROUND WITH BLACK LETTERS, CODE: 39) TO BE STAMPED ON POLYBAG.

PIN OUT	
P1	P2
1	1
2	2
3	3
24	24
25	25
SHELL	SHELL(DRAIN WIRE)

DETAIL A
METRIC SCREWS

RS-232 Cable
DB25 Male to DB25 Female, **ft
C03-25M-25F-25XX

"**" & "XX" SEE CHART 1

CHART 1:

P/N	**	XX	L	T
C03-25M-25F-2503	3	03	914	±25
C03-25M-25F-2506	6	06	1829	±51
C03-25M-25F-2510	10	10	3048	±51
C03-25M-25F-2515	15	15	4572	+152/-51
C03-25M-25F-2524	24	24	7315	+152/-51
C03-25M-25F-2550	50	50	15240	+305/-152



DRAWING APPROVED _____ DATE: _____																								
SAMPLE APPROVED PER _____ DATE: _____ DRAWING SPECIFICATIONS																								
PROPRIETARY & CONFIDENTIAL, THIS DOCUMENT MAY NOT BE COPIED, OR DISCLOSED IN WHOLE OR IN PART WITHOUT THE WRITTEN CONSENT OF TNT.																								
<table border="1"> <tr> <th>SYMBOL</th> <th>UNIT</th> <th>TITLE</th> </tr> <tr> <td>⊕</td> <td>mm</td> <td>DB25M / DB25F</td> </tr> <tr> <td>SCALE</td> <td>1/1</td> <td>CUS. NAME</td> </tr> <tr> <td>SHEET</td> <td>1/1</td> <td>CUS. P/N</td> </tr> <tr> <td colspan="2">DIMENSIONAL TOLERANCES UNLESS OTHERWISE NOTED</td> <td rowspan="2">C03-25M-25F-25**</td> </tr> <tr> <td>X± 0.2</td> <td>.XX±</td> </tr> <tr> <td>XXX±</td> <td>ANGLES±</td> <td>DRAW NO.</td> </tr> <tr> <td>REV. A</td> <td>CUS.REV A</td> <td>P9907019-E</td> </tr> </table>	SYMBOL	UNIT	TITLE	⊕	mm	DB25M / DB25F	SCALE	1/1	CUS. NAME	SHEET	1/1	CUS. P/N	DIMENSIONAL TOLERANCES UNLESS OTHERWISE NOTED		C03-25M-25F-25**	X± 0.2	.XX±	XXX±	ANGLES±	DRAW NO.	REV. A	CUS.REV A	P9907019-E	
SYMBOL	UNIT	TITLE																						
⊕	mm	DB25M / DB25F																						
SCALE	1/1	CUS. NAME																						
SHEET	1/1	CUS. P/N																						
DIMENSIONAL TOLERANCES UNLESS OTHERWISE NOTED		C03-25M-25F-25**																						
X± 0.2	.XX±																							
XXX±	ANGLES±	DRAW NO.																						
REV. A	CUS.REV A	P9907019-E																						
<input type="checkbox"/> O <input type="checkbox"/> S	<table border="1"> <tr> <td>ENG.</td> <td>DATE</td> </tr> <tr> <td>CHECKED</td> <td>DATE</td> </tr> <tr> <td>APPROVED</td> <td>DATE</td> </tr> </table>	ENG.	DATE	CHECKED	DATE	APPROVED	DATE																	
ENG.	DATE																							
CHECKED	DATE																							
APPROVED	DATE																							