



- NOTE:
1. CABLE: 28AWG X 25C, AL-FOIL SHIELDED WITH DRAIN WIRE, NON-UL, BEIGE (CTG-401) PVC JACKET.
 2. CONNECTOR: P1 & P2: D-SUB 25PIN MALE: SOLDER TYPE, GOLD FLASH CONTACTS;
 3. THUMB SCREW TO BE MOLDED.
 4. SHIELDING: AL-FOIL TAPE COVER PREMOLD AND 100% CONTACT WITH SHELL.
 5. ALL HOOD: MOLDED BEIGE(CTG-401) PVC.
 6. PACKING: 1. 4PCS METRIC(M2.6) SCREW IN A CLEAR POLYBAG, SEALED, LABEL (WHITE BACKGROUND WITH BLACK LETTERS, SEE "DETAIL A") TO BE STAMPED ON POLYBAG.
2. EACH CABLE & PACKAGED SCREW IN A TNT PRINTED ZIP-LOCK POLY-BAG.
BAR CODE LABEL (WHITE BACKGROUND WITH BLACK LETTERS, CODE: 39) TO BE STAMPED ON POLYBAG.

DETAIL A
METRIC SCREWS

RS-232 Cable
DB25 Male to DB25 Male, **ft
C03-25M-25M-25XX

** & XX SEE CHART 1

PIN OUT

P1	P2
1	1
2	2
3	3
...	...
24	24
25	25
SHELL	SHELL(DRAIN WIRE)

CHART 1:

P/N	**	XX	L	T
C03-25M-25M-2503	3	03	914	±25
C03-25M-25M-2506	6	06	1829	±51
C03-25M-25M-2510	10	10	3048	±51
C03-25M-25M-2515	15	15	4572	+152/-51
C03-25M-25M-2524	24	24	7315	+152/-51
C03-25M-25M-2550	50	50	15240	+305/-152
C03-25M-25M-2575	75	75	22860	+305/-152
C03-25M-25M-25100	100	100	30480	+305/-152



O
 S

DRAWING APPROVED _____		DATE: _____	
SAMPLE APPROVED PER _____		DATE: _____	
PROPRIETARY & CONFIDENTIAL, THIS DOCUMENT MAY NOT BE COPIED, OR DISCLOSED IN WHOLE OR IN PART WITHOUT THE WRITTEN CONSENT OF TNT.			
	mm	TITLE DB25M / DB25M	
SCALE		CUS. NAME	
SHEET	1/1	ENG. _____ DATE _____	
DIMENSIONAL TOLERANCES UNLESS OTHERWISE NOTED		CUS. P/N	
X± 0.2	.XX±	C03-25M-25M-25**	
XXX±	ANGLES±	CHECKED _____ DATE _____	
REV. A	CUS.REV A	DRAW NO. P9907018-E	
		APPROVED _____ DATE _____	