



NOTE:

- ① CABLE: 28AWG X 9C, AL-FOIL SHIELDED WITH DRAIN WIRE, NON-UL, BEIGE (CTG-401) PVC JACKET.
- 2. CONNECTOR: P1: D-SUB 9PIN FEMALE: SOLDER TYPE, GOLD FLASH CONTACTS; BLACK PBT INSULATION.
P2: D-SUB 25PIN MALE: SOLDER TYPE, GOLD FLASH CONTACTS. BLACK PBT INSULATION.
- ③ THUMB SCREW TO BE MOLDED.
- 4. SHIELDING: AL-FOIL TAPE COVER PREMOLD AND 100% CONTACT WITH CONNECTOR SHELL.
- 5. ALL HOOD: MOLDED BEIGE(CTG-401) PVC.
- 6. TESTING: 100% ELECTRICAL TEST AT 1M OHM INSULATION RESISTANCE.
- 7. PACKING: 1. 2PCS METRIC(M2.6) SCREW IN A CLEAR POLYBAG, SEALED, LABEL (WHITE BACKGROUND WITH BLACK LETTERS, SEE "DETAIL A") TO BE STAMPED ON POLYBAG.
2. EACH CABLE & PACKAGED SCREW IN A TNT PRINTED ZIP-LOCK POLY-BAG.
BAR CODE LABEL (WHITE BACKGROUND WITH BLACK LETTERS, CODE: 39) TO BE STAMPED ON POLYBAG.

PIN OUT

P1	P2
1	8
2	3
3	2
4	20
5	7
6	6
7	4
8	5
9	22
SHELL	SHELL(DRAIN WIRE)

DETAIL A

METRIC SCREWS

AT Serial Cable
DB25 Male to DB9 Female, XXft

C04-25M-09F-09**

"**" & "XX" SEE CHART 1

CHART 1:

P/N	**	XX	L	T
C04-25M-09F-06	6	06	1829	±51
C04-25M-09F-10	10	10	3048	±51
C04-25M-09F-15	15	15	4572	+152/-51
C04-25M-09F-25	25	25	7620	+152/-51



0
 S

DRAWING APPROVED _____ DATE: _____																													
SAMPLE APPROVED PER _____ DATE: _____ DRAWING SPECIFICATIONS																													
PROPRIETARY & CONFIDENTIAL, THIS DOCUMENT MAY NOT BE COPIED, OR DISCLOSED IN WHOLE OR IN PART WITHOUT THE WRITTEN CONSENT OF TNT.																													
<table border="1"> <tr> <td>⊕</td> <td>mm</td> <td>TITLE</td> <td>DB25M / DB9F</td> </tr> <tr> <td>SCALE</td> <td>↗</td> <td>CUS. NAME</td> <td></td> </tr> <tr> <td>SHEET</td> <td>1/1</td> <td>CUS. P/N</td> <td>C04-25M-09F-09**</td> </tr> <tr> <td colspan="2">DIMENSIONAL TOLERANCES UNLESS OTHERWISE NOTED</td> <td>DRAW NO.</td> <td>P9912065-E</td> </tr> <tr> <td>X± 0.2</td> <td>.XX±</td> <td></td> <td></td> </tr> <tr> <td>XXX±</td> <td>ANGLES±</td> <td></td> <td></td> </tr> <tr> <td>REV. B</td> <td>CUS.REV A</td> <td></td> <td></td> </tr> </table>	⊕	mm	TITLE	DB25M / DB9F	SCALE	↗	CUS. NAME		SHEET	1/1	CUS. P/N	C04-25M-09F-09**	DIMENSIONAL TOLERANCES UNLESS OTHERWISE NOTED		DRAW NO.	P9912065-E	X± 0.2	.XX±			XXX±	ANGLES±			REV. B	CUS.REV A			<p>ENG. _____ DATE _____</p> <p>CHECKED _____ DATE _____</p> <p>APPROVED _____ DATE _____</p>
⊕	mm	TITLE	DB25M / DB9F																										
SCALE	↗	CUS. NAME																											
SHEET	1/1	CUS. P/N	C04-25M-09F-09**																										
DIMENSIONAL TOLERANCES UNLESS OTHERWISE NOTED		DRAW NO.	P9912065-E																										
X± 0.2	.XX±																												
XXX±	ANGLES±																												
REV. B	CUS.REV A																												