



NOTE:

- 1. CABLE: 28AWG X 9C, AL-FOIL SHIELDED WITH DRAIN WIRE, NON-UL, BEIGE (CTG-401) PVC JACKET.
- 2. CONNECTOR: P1: D-SUB 9PIN MALE: SOLDER TYPE, GOLD FLASH CONTACTS; P2: D-SUB 25PIN MALE: SOLDER TYPE, GOLD FLASH CONTACTS.
- 3. THUMB SCREW TO BE MOLDED.
- 4. SHIELDING: AL-FOIL TAPE COVER PREMOLD AND 100% CONTACT WITH SHELL.
- 5. ALL HOOD: MOLDED BEIGE(CTG-401) PVC.
- 6. PACKING: 1. 2PCS METRIC(M2.6) SCREW IN A CLEAR POLYBAG, SEALED, LABEL (WHITE BACKGROUND WITH BLACK LETTERS, SEE "DETAIL A") TO BE STAMPED ON POLYBAG. 2. EACH CABLE & PACKAGED SCREW IN A TNT PRINTED ZIP-LOCK POLY-BAG. BAR CODE LABEL (WHITE BACKGROUND WITH BLACK LETTERS, CODE: 39) TO BE STAMPED ON POLYBAG.

PIN OUT

P1	P2
1	8
2	3
3	2
4	20
5	7
6	6
7	4
8	5
9	22
SHELL	SHELL(DRAIN WIRE)

DETAIL A

METRIC SCREWS

AT Serial Cable  
DB25 Male to DB9 Male, \*\*ft

C04-25M-09M-09XX

"\*\*" & "XX" SEE CHART 1

CHART 1:

P/N	**	XX	L	T
C04-25M-09M-906	6	06	1829	±51
C04-25M-09M-910	10	10	3048	±51
C04-25M-09M-915	15	15	4572	+152/-51
C04-25M-09M-925	25	25	7620	+152/-51



0  
 S

DRAWING APPROVED _____ DATE: _____		TITLE DB25M / DB9M	
SAMPLE APPROVED PER _____ DATE: _____		CUS. NAME	
PROPRIETARY & CONFIDENTIAL, THIS DOCUMENT MAY NOT BE COPIED, OR DISCLOSED IN WHOLE OR IN PART WITHOUT THE WRITTEN CONSENT OF TNT.			
	mm	DIMENSIONAL TOLERANCES UNLESS OTHERWISE NOTED	
SCALE		CUS. P/N C04-25M-09M-09**	
SHEET	1/1	DRAW NO. P9907026-E	
X±	.XX±		
XXX±	ANGLES±		
REV. A	CUS.REV	ENG. _____ DATE _____	CHECKED _____ DATE _____
		APPROVED _____ DATE _____	