



NOTE:

1. CABLE: 28AWG X 36C, AL-FOIL SHIELDED WITH DRAIN WIRE, NON-UL, BEIGE (CTG-401) PVC JACKET.
2. CONNECTOR: P1 & P2: CENTRONICS 36PIN FEMALE: SOLDER TYPE, GOLD FLASH CONTACTS.
3. SHIELDING: AL-FOIL TAPE COVER PREMOLD AND 100% CONTACT WITH SHELL.
4. ALL HOOD: MOLDED BEIGE(CTG-401) PVC.
5. PACKING: EACH CABLE IN A TNT PRINTED ZIP-LOCK POLY-BAG. BAR CODE LABEL (WHITE BACKGROUND WITH BLACK LETTERS, CODE: 39) TO BE STAMPED ON POLYBAG.

FEMALE BAIL LOCK HARDWARE(X4)

PIN OUT

P1	P2
1	1
2	2
3	3
35	35
36	36
SHELL	SHELL(DRAIN WIRE)

Centronics Parallel Cable
Cent. 36 Female to Cent. 36 Female, **ft

C05-36F-36F-36XX

** & XX SEE CHART 1

CHART 1:

P/N	**	XX	L	T
C05-36F-36F-3606	6	06	1829	±51
C05-36F-36F-3610	10	10	3048	±51
C05-36F-36F-3612	12	12	3658	+152/-51
C05-36F-36F-3625	25	25	7620	+152/-51
C05-36F-36F-3650	50	50	15240	+305/-152



- O
- S

DRAWING APPROVED _____ DATE: _____		TITLE CN36F / CN36F	
SAMPLE APPROVED PER _____ DATE: _____		CUS. NAME	
PROPRIETARY & CONFIDENTIAL, THIS DOCUMENT MAY NOT BE COPIED, OR DISCLOSED IN WHOLE OR IN PART WITHOUT THE WRITTEN CONSENT OF TNT.			
	mm	CUS. P/N C05-36F-36F-36**	
SCALE			
SHEET	1/1	DRAW NO. P9912049-E	ENG. _____ DATE _____
DIMENSIONAL TOLERANCES UNLESS OTHERWISE NOTED			CHECKED _____ DATE _____
X± 0.2	.XX±	APPROVED _____ DATE _____	
.XXX±	ANGLES±		
REV. A	CUS.REV		