



- NOTE:
1. CABLE: 28AWG X 36C, AL-FOIL SHIELDED WITH DRAIN WIRE, NON-UL, BEIGE (CTG-401) PVC JACKET.
 2. CONNECTOR: P1: CENTRONICS 36PIN MALE: SOLDER TYPE, GOLD FLASH CONTACTS; P2: CENTRONICS 36PIN FEMALE: SOLDER TYPE, GOLD FLASH CONTACTS.
 3. SHIELDING: AL-FOIL TAPE COVER PREMOLD AND 100% CONTACT WITH SHELL.
 4. ALL HOOD: MOLDED BEIGE(CTG-401) PVC.
 5. PACKING: EACH CABLE IN A TNT PRINTED ZIP-LOCK POLY-BAG. BAR CODE LABEL (WHITE BACKGROUND WITH BLACK LETTERS) TO BE STAMPED ON POLYBAG.

FEMALE BAIL LOCK HARDWARE(X2)

PIN OUT	
P1	P2
1	1
2	2
3	3
35	35
36	36
SHELL	SHELL(DRAIN WIRE)

Centronics Parallel Cable
Cent. 36 Male to Cent. 36 Female, **ft

C05-36M-36F-36XX

"**" & "XX" SEE CHART 1

CHART 1:

P/N	**	XX	L	T
C05-36M-36F-3606	6	06	1829	±51
C05-36M-36F-3610	10	10	3048	±51
C05-36M-36F-3612	12	12	3658	+152/-51
C05-36M-36F-3615	15	15	4572	+152/-51
C05-36M-36F-3624	24	24	7315	+152/-51
C05-36M-36F-3625	25	25	7620	+152/-51
C05-36M-36F-3650	50	50	15240	+305/-152



DRAWING APPROVED _____		DATE: _____	
SAMPLE APPROVED PER _____		DATE: _____	
DRAWING SPECIFICATIONS			
PROPRIETARY & CONFIDENTIAL, THIS DOCUMENT MAY NOT BE COPIED, OR DISCLOSED IN WHOLE OR IN PART WITHOUT THE WRITTEN CONSENT OF TNT.			
	mm	TITLE CN36M / CN36F	
SCALE		CUS. NAME	
SHEET	1/1	CUS. P/N	
DIMENSIONAL TOLERANCES UNLESS OTHERWISE NOTED		C05-36M-36F-36**	
X± 0.2	.XX±	DRAW NO.	
.XXX±	ANGLES±	P9907041-E	
REV. ø	CUS.REV	APPROVED _____	
		DATE _____	

