

NOTE:


- 1. CABLE: 28AWG X 9C, AL-FOIL SHIELDED WITH DRAIN WIRE, NON-UL, BEIGE (CTG-401) PVC JACKET.
- 2. CONNECTOR: P1:D-SUB 9PIN MALE:SOLDER TYPE,GOLD FLASH CONTACTS.  
P2:D-SUB 9PIN FEMALE:SOLDER TYPE,GOLD FLASH CONTACTS.
- 3. THUMB SCREW TO BE MOLDED.
- 4. SHIELDING: AL-FOIL TAPE COVER PREMOLD AND 100% CONTACT WITH SHELL.
- 5. ALL HOOD: MOLDED BEIGE(CTG-401) PVC.
- 6. PACKING: EACH CABLE IN A TNT PRINTED ZIP-LOCK POLY-BAG. BAR CODE LABEL (WHITE BACKGROUND WITH BLACK LETTERS, CODE: 39) TO BE STAMPED ON POLYBAG.

PIN OUT

P1	P2
1	1
2	2
3	3
4	4
5	5
6	6
7	7
8	8
9	9

SHELL ——— SHELL(DRAIN WIRE)

AT Serial Cable  
DB9 MALE TO DB9 FEMALE, \*\*FT




C06-09M-09F-XX

"XX" & "\*\*" SEE CHART 1



CHART 1:

C06-09M-09F-915	15	15	4572	+152/-51	<input type="checkbox"/> 0
C06-09M-09F-910	10	10	3048	±51	<input type="checkbox"/> 0
C06-09M-09F-906	6	06	1829	±51	<input type="checkbox"/> S
P/N	**	XX	L	T	

DRAWING APPROVED _____ DATE: _____		SAMPLE APPROVED PER _____ DATE: _____				
PROPRIETARY & CONFIDENTIAL. THIS DOCUMENT MAY NOT BE COPIED, OR DISCLOSED IN WHOLE OR IN PART WITHOUT THE WRITTEN CONSENT OF TNT.						
<table border="1"> <tr><td>mm</td></tr> <tr><td>SCALE NONE</td></tr> <tr><td>SHEET 1/1</td></tr> </table>	mm	SCALE NONE	SHEET 1/1	TITLE DB9M TO DB9F		
mm						
SCALE NONE						
SHEET 1/1						
DIMENSIONAL TOLERANCES UNLESS OTHERWISE NOTED		CUS. NAME				
.X ± 0.2	.XX ±	CUS. P/N C06-09M-09F-XX				
.XXX ±	ANGLES ±	PART NO.	ENG. _____ DATE _____			
REV. C	CUS. REV		CHECKED _____ DATE _____			
			APPROVED _____ DATE _____			