



NOTE:

1. CABLE: 28AWG X 15C, AL-FOIL SHIELDED WITH DRAIN WIRE, NON-UL, BEIGE (CTG-401) PVC JACKET.
2. CONNECTOR: P1: HIGH DENSITY D-SUB 15PIN MALE: SOLDER TYPE, GOLD FLASH CONTACTS; P2: HIGH DENSITY D-SUB 15PIN FEMALE: SOLDER TYPE, GOLD FLASH CONTACTS.
3. THUMB SCREW TO BE MOLDED.
4. SHIELDING: AL-FOIL TAPE COVER PREMOLD AND 100% CONTACT WITH SHELL.
5. ALL HOOD: MOLDED BEIGE(CTG-401) PVC.
6. PACKING: EACH CABLE IN A TNT PRINTED ZIP-LOCK POLY-BAG. BAR CODE LABEL (WHITE BACKGROUND WITH BLACK LETTERS, CODE: 39) TO BE STAMPED ON POLYBAG.

PIN OUT	
P1	P2
1	1
2	2
3	3
4	4
5	5
6	6
7	7
8	8
9	9
10	10
11	11
12	12
13	13
14	14
15	15
SHELL	SHELL(DRAIN WIRE)

VGA Monitor Cable
High Density DB15 Male to Female, **ft

C06-HD15M-HD15F-XX

"**" & "XX" SEE CHART 1

CHART 1:

P/N	**	XX	L	T
C06-HD15M-HD15F-01	1	01	305	+25/-13
C06-HD15M-HD15F-06	6	06	1829	±51
C06-HD15M-HD15F-10	10	10	3048	±51
C06-HD15M-HD15F-15	15	15	4572	+152/-51
C06-HD15M-HD15F-25	25	25	7620	+152/-51
C06-HD15M-HD15F-50	50	50	15240	+305/-152



DRAWING APPROVED _____		DATE: _____	
SAMPLE APPROVED PER _____		DATE: _____	
PROPRIETARY & CONFIDENTIAL, THIS DOCUMENT MAY NOT BE COPIED, OR DISCLOSED IN WHOLE OR IN PART WITHOUT THE WRITTEN CONSENT OF TNT.			
	mm	TITLE	
SCALE		HD15M/F	
SHEET	1/1	CUS. NAME	
DIMENSIONAL TOLERANCES UNLESS OTHERWISE NOTED		CUS. P/N	
X± 0.2	.XX±	C06-HD15M-HD15F-**	
XXX±	ANGLES±	DRAW NO.	
REV. A	CUS.REV A	P9907028-E	
		APPROVED _____	DATE _____