

NOTE:


- 1. CABLE: 28AWG X 5C, AL-FOIL SHIELDED WITH DRAIN WIRE, NON-UL, BEIGE (CTG-401) PVC JACKET.
- 2. CONNECTOR: P1: DIN 5PIN MALE: SOLDER TYPE, NICKEL PLATED CONTACTS; P2: DIN 5PIN FEMALE: SOLDER TYPE, NICKEL PLATED CONTACTS.
- 3. SHIELDING: AL-FOIL TAPE COVER PREMOLD AND 100% CONTACT WITH SHELL.
- 4. ALL HOOD: MOLDED BEIGE(CTG-401) PVC.
- 5. PACKING: EACH CABLE IN A TNT PRINTED ZIP-LOCK POLY-BAG. BAR CODE LABEL (WHITE BACKGROUND WITH BLACK LETTERS, CODE: 39) TO BE STAMPED ON POLYBAG.

PIN OUT

P1	P2
1	1
2	2
3	3
4	4
5	5

SHELL ——— SHELL(DRAIN WIRE)

PC/AT Keyboard Cable
Reg. DIN5 Male to Female, **ft



C07-D5M-D5F-XX

“**” & “XX” SEE CHART 1

CHART 1:

C07-D5M-D5F-25	25	25	7620	+152/-51
C07-D5M-D5F-15	15	15	4572	+152/-51
C07-D5M-D5F-10	10	10	3048	±51
C07-D5M-D5F-06	6	06	1829	±51
C07-D5M-D5F-01	1	01	305	+25/-13
P/N	**	XX	L	T



0
 S

DRAWING APPROVED _____		DATE: _____	
SAMPLE APPROVED PER _____		DRAWING SPECIFICATIONS _____	
PROPRIETARY & CONFIDENTIAL. THIS DOCUMENT MAY NOT BE COPIED, OR DISCLOSED IN WHOLE OR IN PART WITHOUT THE WRITTEN CONSENT OF TNT.			
	mm	TITLE DIN5M/F	
SCALE	NONE	CUS. NAME	
SHEET	1/1	CUS. P/N C07-D5M-D5F-**	
DIMENSIONAL TOLERANCES UNLESS OTHERWISE NOTED		PART NO. P9907037-E	
.X ±	.XX ±	ENG. _____ DATE _____	
.XXX ±	ANGLES ±	CHECKED _____ DATE _____	
REV. A	CUS. REV. A	APPROVED _____ DATE _____	

