

CHART1:

P/N	FT	L(mm)	T(mm)
C07-D5M-D5M-006	6	1829	±51
C07-D5M-D5M-010	10	3048	±51
C07-D5M-D5M-015	15	4572	+152/-51
C07-D5M-D5M-025	25	7620	+152/-51
C07-D5M-D5M-075	75	22860	+305/-152
C07-D5M-D5M-100	100	30480	+305/-152


PIN OUT

P1	P2
1	1 BLACK
2	2 BROWN
4	4 RED
5	5 ORANGE
SHELL	SHELL(DRAIN WIRE)

NOTE:

1. CABLE: 28AWG X 4C, AL-FOIL SHIELDED WITH DRAIN WIRE, NON-UL, BEIGE (TNT-BG-03) PVC JACKET.OD:5.0±0.15mm
2. CONNECTOR: P1&P2: DIN 5PIN MALE: SOLDER TYPE, GOLD FLASH CONTACTS; NICKEL PLATED SHELL
3. SHIELDING: AL-FOIL TAPE COVER PREMOLD AND 100% CONTACT WITH SHELL.
4. ALL HOOD: MOLDED BEIGE(TNT-BG-03) PVC.MOLD:BORROWED
5. PACKING: EACH CABLE IN A TNT PRINTED ZIP-LOCK POLY-BAG.



TOLERANCE		M/M		TNT Tri-Net Technology, Inc.			
INCHES				http://www.trinetusa.com			
.X	.015	.30		SCALE	NONE	 REV   A	
.XX	.010	.10		UNIT	MM		
.XXX	.005	.05		SHEET	1/1		
DRAWN BY				DATE	06/20/05	DWG NO.	
CHECK BY				TITLE			DIN5M TO DIN5M
APPD BY				PART NO.			C07-D5M-D5M-XX