


NOTE:

- ①. CABLE: 28AWG X 6C, AL-FOIL SHIELDED WITH DRAIN WIRE, NON-UL, BEIGE (CTG-401) PVC JACKET.
- 2. CONNECTOR: P1: MINI DIN 6PIN MALE: SOLDER TYPE, GOLD FLASH CONTACTS; P2: MINI DIN 6PIN FEMALE: SOLDER TYPE, GOLD FLASH CONTACTS.
- 3. SHIELDING: AL-FOIL TAPE COVER PREMOLD AND 100% CONTACT WITH SHELL.
- 4. ALL HOOD: MOLDED BEIGE(CTG-401) PVC.
- 5. PACKING: EACH CABLE IN A TNT PRINTED ZIP-LOCK POLY-BAG. BAR CODE LABEL (WHITE BACKGROUND WITH BLACK LETTERS, CODE: 39) TO BE STAMPED ON POLYBAG.

PIN OUT	
P1	P2
1	1
2	2
3	3
4	4
5	5
6	6
SHELL	SHELL(DRAIN WIRE)

PS/2 Keyboard Cable
Mini DIN6 Male to Female, **ft



C08-MD6M-MD6F-XX

"**" & "XX" SEE CHART 1

CHART 1:

P/N	**	XX	L	T
C08-MD6M-MD6F-01	1	01	305	+25/-13
C08-MD6M-MD6F-06	6	06	1829	±51
C08-MD6M-MD6F-10	10	10	3048	±51
C08-MD6M-MD6F-15	15	15	4572	+152/-51
C08-MD6M-MD6F-25	25	25	7620	+152/-51
C08-MD6M-MD6F-50	50	50	15240	+305/-152
C08-MD6M-MD6F-75	75	75	22860	+305/-152
C08-MD6M-MD6F-100	100	100	30480	+305/-152



DRAWING APPROVED _____		DATE: _____	
SAMPLE APPROVED PER _____		DRAWING SPECIFICATIONS _____	
PROPRIETARY & CONFIDENTIAL. THIS DOCUMENT MAY NOT BE COPIED, OR DISCLOSED IN WHOLE OR IN PART WITHOUT THE WRITTEN CONSENT OF TNT.			
	mm	TITLE	MD6M/F
SCALE	NONE	CUS. NAME	
SHEET	1/1	CUS. P/N	
DIMENSIONAL TOLERANCES UNLESS OTHERWISE NOTED		C08-MD6M-MD6F-**	
<input type="checkbox"/> 0	.X ± 0.2	ANGLES ±	ENG. _____ DATE _____
<input type="checkbox"/> S	.XXX ±	CUS. REV. A	CHECKED _____ DATE _____
REV. A	CUS. REV. A	PART NO.	APPROVED _____ DATE _____
		P9907030-E	