



PIN OUT

P1	P2	P3	P1	P2	P3
1	1	1	5	5	5
6	6	6	11	11	11
2	2	2	12	12	12
7	7	7	10	10	10
3	3	3	13	13	13
8	8	8	14	14	14
4	4	4	15	15	15
			SHELL	SHELL	SHELL
					(DRAIN+BRAID)

NOTE:

- CABLE: UL 20276 (32AWG*1C)*3+30AWG*2P+30AWG*5C+ AEB
OD=5.0±0.1mm JACKET:BLACK(TNT-BK)
- CONN. : P1 : HIGH DENSITY D-SUB 15PIN MALE: SOLDER TYPE, GOLD FLASH CONTACTS. PBT BLACK.
P2&P3 : HIGH DENSITY D-SUB 15PIN FEMALE: SOLDER TYPE, GOLD FLASH CONTACTS. PBT BLACK.
- THUMB SCREW TO BE MOLDED BLACK(TNT-BK).
- ALL HOOD: MOLDED BLACK(TNT-BK) PVC.
- PACKING: EACH CABLE IN A TNT PRINTED POLY-BAG.
- MOLD NO: INNER MOLDING: TNT-DB9-N01
OUTER MOLDING: TNT-DB9-01



TOLERANCE		INCHES		M/M		TNT Tri-Net Technology, Inc.			
.X	.015			.30		http://www.trinetusa.com			
.XX	.010			.10		SCALE	NONE	REV	A
.XXX	.005			.05		UNIT	MM		
DRAWN BY		SHEET		1/2		DWG NO.			
CHECK BY		DATE		02/18/05		TITLE			
APPD BY		PART NO.		HDB15M TO 2*HDB15F					
				C18-Y-MFF-008					