



NOTE:

- 1.CABLE: UL2919 28AWG*8C+1+B NAVY BLUE JACKET OD=5.5mm
- 2.CONN 1: RJ45(8P8C) MALE SHIELDED PLUG
- 3.CONN 2: HPDB68PIN MALE BLACK INSULATION(MOLDING)
- 4.PRO MOLD: PE
- 5.COPPER FOIL:22*140mm, 360° SOLDER
- 6.MOLDING: NAVY BLUE PVC(45P)
- 7.SCREW: #4-40UNC 4*40.5mm NAVY BLUE
- 8.LABEL: PRINTER"1, 2, 3...8"



| TOLERANCE | | | | | | |
|-----------|--------|-----|----------|------------------------|---------|---|
| | INCHES | M/M | | | | |
| .X | .015 | .30 | | | | |
| .XX | .010 | .10 | SCALE | NONE | | |
| .XXX | .005 | .05 | UNIT | MM | REV | A |
| DRAWN BY | | | SHEET | 1/1 | DWG NO. | |
| CHECK BY | | | DATE | 11/27/05 | | |
| APPD BY | | | TITLE | HPDB68M TO 8P8C PLUG*8 | | |
| | | | PART NO. | C20-OCTAL-ASYNC10 | | |

TNT Tri-Net Technology, Inc.
<http://www.trinetusa.com>