

4P MALE

4P FEMALE


4P FEMALE

| P2 | P1 | P3 | COLOR  |
|----|----|----|--------|
| 1  | 1  | 1  | YELLOW |
| 2  | 2  | 2  | BLACK  |
| 3  | 3  | 3  | BLACK  |
| 4  | 4  | 4  | RED    |

NOTES:

1. WIRE: UL1007 VW-1 80°C 300V 18AWG.
2. P1: HOUSING: 4PIN, FEMALE, PITCH 5.08MM, NATURAL.  
TERMINAL: MALE, BARSS, TIN PLATED.
- P2 & P3: HOUSING: 4PIN, MALE, PITCH 5.08MM,  
NATURAL.  
TERMINAL: FEMALE, BASS, TIN PLATED.



| TOLERANCE |      |     | Tri-Net Technology, Inc.  |      |   |     |   |
|-----------|------|-----|---|------|---|-----|---|
| INCHES    | M    | M   | <a href="http://www.trinetusa.com">http://www.trinetusa.com</a> |      |   |     |   |
| .X        | .015 | .30 | SCALE   | NONE |  | REV | A |
| .XX       | .010 | .10 | UNIT  | MM   |   |     |   |
| .XXX      | .005 | .05 | SHEET 1/1   |      | DWG NO.   |     |   |
| DRAWN BY  |      |     | DATE 07/05/06   |      | TITLE   |     |   |
| CHECK BY  |      |     | 5.25" M TO TWO 5.25" F  |      |   |     |   |
| APPD BY   |      |     | PART NO. C26-Y-555-XX   |      |   |     |   |