


P/N	XX(FT)	L(MM)	TOLERANCE(MM)
C33-BNC-MM-03	03	914	+25/-25
C33-BNC-MM-06	06	1829	+50/-50
C33-BNC-MM-10	10	3048	+100/-75
C33-BNC-MM-15	15	4572	+150/-100
C33-BNC-MM-25	25	7620	+150/-100

PIN OUT :



NOTE:

- 1.CABLE:RG59B/U CONDUCTOR:(1/0.58 BARE COPPER)+PE INSULATION+ BRAID(16*7/0.12),PVC JACKET,COLOR:BLACK, $\phi 6.0 \pm 0.15$ mm.
TNT P/N:B-RG59BU-PE-B-BK-01
- 2.CONN.:P1&P2: BNC MALE, GOLD FLASH CONTACT,INSULATOR:WHITE GOLD PLATED SHELL,75 OHM.(RG59U)
- 3.ASS'Y BOOT: 45P PVC BLACK.MOLDED NO:P1&P2:TNT-F180-01.
- 4.TESTING:100% ELECTRICAL TEST.
- 5.PACKING:EACH CABLE IN A POLY-BAG.



TOLERANCE		INCHES		M/M		TNT Tri-Net Technology		http://www.trinetusa.com	
.X	.015	.30		SCALE	NONE	REV A	DWG NO.		
.XX	.010	.10		UNIT	MM				
.XXX	.005	.05		SHEET	1/2				
DRAWN BY	LANCE			DATE	08/13/05				
CHECK BY				TITLE	BNCM TO BNCM				
APPD BY				PART NO.	C33-BNC-MM-XX				