



NOTE:

- 1. CABLE: 28AWG X 9PAIRS, AL-FOIL AND BRAID SHIELDED WITH A DRAIN WIRE, UL CL2 + CSA FT4, BLUE(CTG-615, PANTONE/#300C) PVC JACKET.
- 2. CONNECTOR: P1: CISCO 26PIN MALE: 1.0mm PITCH, GOLD FLASH CONTACTS, WHITE PBT INSULATION.
P2: V.35 MALE: CRIMP TYPE, GOLD FLASH CONTACTS, BLACK PBT INSULATION, WITH SHELL.
- 3. METAL SCREW.
- 4. METAL SCREW LOCK.
- 5. SHIELDING: COPPER FOIL TAPE COVER PREMOLD AND POINT SOLDER TO CONNECTOR SHELL, 360° SOLDER TO CABLE BRAID.
- 6. ALL HOOD: MOLDED BLUE(CTG-615, PANTONE/#300C) PVC.
- 7. TESTING: 100% ELECTRICAL TEST AT 1M OHM INSULATION RESISTANCE.
- 8. PACKING: EACH CABLE IN A PE POLY-BAG. LABEL (WHITE BACKGROUND WITH BLACK LETTERS) TO BE STAMPED ON PE POLY-BAG.



TOLERANCE INCHES			M/M		Tri-Net Technology, Inc. http://www.trinetusa.com			
.X	.015	.30	SCALE	NONE			REV	D
.XX	.010	.10	UNIT	MM				
.XXX	.005	.05	SHEET	1/2	DWG NO.			
DRAWN BY			DATE	09/12/06				
CHECK BY			TITLE					
APPD BY			PART NO. C20-SS-V35MT					

