



P/N:U03-XX-AB

LENGTH UNIT:FT

PIN OUT

P1 P2

	24AWG	1	1	RED
	28AWG	2	2	WHITE
	28AWG	3	3	GREEN
	24AWG	4	4	BLACK
	SHELL			SHELL(BRAID)

NOTES:

1. CABLE: UL2725 USB 1.1 CABLE, (28AWG*1PAIR + 24AWG X 2C), AL-FOIL AND BRAID SHIELDED WITH A DRAIN WIRE(24AWG), PVC JACKET,COLOR:TNT-BG-02. OD:4.5±0.10mm.
2. CONNECTOR: P1: USB A TYPE MALE, SOLDER TYPE, WHITE PBT INSULATION, GOLD FLASH CONTACTS, NICKEL PLATED SHELL.
P2: USB B TYPE MALE, SOLDER TYPE, WHITE PBT INSULATION, GOLD FLASH CONTACTS, NICKEL PLATED SHELL.
3. HOOD: MOLDED TNT-BG-02 PVC.
4. PACKING:EACH CABLE IN A PRINTED ZIP-LOCK POLY-BAG.
5. 100% ELECTRICAL TESTING.

L(mm)	T(mm)
L<=1M	+25/-0
1M<L<=3M	+51/-0
3M<L<=5M	+152/-0

TOLERANCE			Tri-Net Technology, Inc.				
INCHES		M/M	http://www.trinetusa.com				
.X	.015	.30	SCALE	NONE		REV	A
.XX	.010	.10	UNIT	MM			
.XXX	.005	.05	SHEET	1/1			
DRAWN BY			DATE	06/18/05	DWG NO.		
CHECK BY			TITLE				
APPD BY			PART NO. U03-XX-AB				

