



L(mm)	T(mm)
L≤1M	+25/-0
1M<L≤3M	+51/-0
3M<L≤5M	+152/-0

PIN OUT

	P1		P2	
20AWG	1	—	1	RED
28AWG	2	—	2	WHITE
28AWG	3	—	3	GREEN
20AWG	4	—	4	BLACK
	SHELL	—	SHELL(BRAID)	



NOTES:

- CABLE: UL2725 USB 2.0 REV CABLE.(28AWG*1PAIR + 24AWG X 2C), AL-FOIL AND BRAID SHIELDED WITH A DRAIN WIRE(24AWG), BLACK(TNT-BK) PVC JACKET, OD:4.8±0.10mm..
- CONNECTOR: P1 : USB 2.0 REV A TYPE MALE, SOLDER TYPE, WHITE PBT INSULATION, GOLD PLATED CONTACTS 30U", NICKEL PLATED SHELL.
P2 : USB 2.0 REV A TYPE FEMALE, SOLDER TYPE, WHITE PBT INSULATION, GOLD PLATED CONTACTS 30U", NICKEL PLATED SHELL.
- HOOD: MOLDED 45P BLACK(TNT-BK) PVC.
- 100% ELECTRICAL TESTING.

TOLERANCE			Tri-Net Technology, Inc.				
INCHES		M/M	http://www.trinetusa.com				
.X	.015	.30	SCALE	NONE		REV	A
.XX	.010	.10	UNIT	MM			
.XXX	.005	.05	SHEET	1/1		DWG NO.	
DRAWN BY			DATE	06/18/05			
CHECK BY			TITLE USB AM TO USB AF				
APPD BY			PART NO. U03-XX-AMAF				

