


Notes: There`s IC inside

No need to make electric test

NOTES:

1. CABLE: UL2725 USB 1.1 REV CABLE. (28AWG\*1PAIR + 24AWG X 2C), AL-FOIL AND BRAID SHIELDED WITH A DRAIN WIRE(24AWG), TRANSPARENCE PVC JACKET, OD:4.5±0.1mm.
2. CONNECTOR:P1:D-SUB 9PIN MALE, SOLDER TYPE, GOLD FLASH CONTACTS, BLACK PBT INSULATION.  
P2:USB A TYPE MALE, SOLDER TYPE, WHITE PBT INSULATION, GOLD PLATED CONTACTS, NICKEL PLATED SHELL.
3. HOOD: MOLDED 45P TRANSPARENCE BLUE PVC.

TOLERANCE		INCHES		M/M		TNT Tri-Net Technology, Inc.		http://www.trinetusa.com	
. X	. 015	. 010	. 10	SCALE	NONE		REV	A	DWG NO.
. XX	. 010	. 10	. 05	UNIT	MM				
. XXX	. 005	. 05		SHEET	1/2				
DRAWN BY				DATE	12/07/04				
CHECK BY				TITLE		USB AM TO DB 9M			
APPD BY				PART NO.		U04-DB9-06			

