



Notes: There`s IC inside

No need to make electric test

NOTES:

1. CABLE:UL2725 USB 1.1 REV CABLE.(28AWG*1PAIR + 24AWG X 2C)+AEB, BEIGE(TNT-BG-02) PVC JACKET, OD:4.5±0.1mm.
2. CONNECTOR: P1: USB A TYPE MALE, SOLDER TYPE, WHITE PBT INSULATION, GOLD PLATED CONTACTS, NICKEL PLATED SHELL. P2&P3:MINI DIN 6PIN FEMALE: SOLDER TYPE, GOLD FLASH CONTACTS.
3. OVERMOLD MOLDED 45P PVC BGIGE(TNT-BG-02) PVC.
4. OVERMOLD PVC 45P COLOR:3395C GREEN.
5. OVERMOLD PVC 45P COLOR:2715C PURPLE.

TOLERANCE			Tri-Net Technology, Inc. http://www.trinetusa.com	
INCHES	M/M	SCALE		
.X	.015	.30	UNIT	MM
.XX	.010	.10	SHEET	1/2
.XXX	.005	.05	DATE	12/07/04
DRAWN BY			DWG NO.	
CHECK BY			TITLE USB AM TO MD6F*2	
APPD BY			PART NO. U04-PS2-01	

