



P/N	FT	L(mm)	T(mm)
U08-AM-BM-4INCH	0.33	102	+10/-10
U08-AM-BM-03	03	914	+25/-25
U08-AM-BM-06	06	1829	+51/-51
U08-AM-BM-10	10	3048	+51/-51
U08-AM-BM-15	15	4572	+152/-51

PIN OUT  
P1 ——— P2

24AWG 1 ——— 1 RED  
28AWG 2 ——— 2 WHITE  
28AWG 3 ——— 3 GREEN  
24AWG 4 ——— 4 BLACK  
SHELL ——— SHELL(BRAID)

Ø > PAIR

- NOTES:
1. CABLE: UL2725 USB 2.0 CABLE,(28AWG\*1PAIR + 24AWG X 2C), AL-FOIL AND BRAID SHIELDED WITH A DRAIN WIRE(24AWG), BLACK(TNT-BK) PVC JACKET, OD:4.8±0.10mm..
  2. CONNECTOR: P1 : USB A TYPE MALE, SOLDER TYPE, WHITE PBT INSULATION, GOLD PLATED CONTACTS,NICKEL PLATED SHELL. P2 : USB B TYPE MALE, SOLDER TYPE, WHITE PBT INSULATION, GOLD PLATED CONTACTS, NICKEL PLATED SHELL.
  3. HOOD: MOLDED 45P BLACK(TNT-BK) PVC.

TOLERANCE		M/M		Tri-Net Technology, Inc.	
INCHES				http://www.trinetusa.com	
.X	.015	.30			
.XX	.010	.10			
.XXX	.005	.05			
DRAWN BY		SHEET	1/1	DWG NO.	
DATE	06/17/05				
CHECK BY		TITLE	USB A/M TO USB B/M 2.0		
APPD BY		PART NO.	U08-AM-BM-XX		

