

NOTES:

1. CABLE: UL2725 USB 2.0 REV CABLE.(28AWG*1PAIR + 28AWG X 2C), AL-FOIL AND BRAID SHIELDED WITH A DRAIN WIRE(28AWG), BLACK(TNT-BK) PVC JACKET, OD:0.15±0.004”(3.8±0.1mm).
2. CONNECTOR: P1:USB A TYPE MALE, SOLDER TYPE, WHITE PBT INSULATION, GOLD PLATED CONTACTS, NICKEL PLATED SHELL.
P2:MINI USB 2.0 REV B TYPE 5P MALE,SOLDER TYPE, PBT INSULATION, GOLD PLATED CONTACTS, NICKEL PLATED SHELL.
3. HOOD: MOLDED 45P PVC BLACK(TNT-BK) PVC.
4. PACKING:EACH CABLE IN A TNT PRINTING ZIP-LOCK POLY-BAG.
5. 100% ELECTRICAL TESTING.
6. MOLD NO:TNT-USB-AM01,TNT-UMBM-01.

PIN OUT :

	P1		P2	
28AWG 1	—————	1	RED	
28AWG 2	—○—	2	WHITE	
28AWG 3	—○—	3	GREEN	
28AWG 4	—————	5	BLACK	
SHELL	—————		SHELL(BRAID)	




CHART:

P/N	xx	**	L	T
U08-AM-MBM-03	3	03	914	±25
U08-AM-MBM-06	6	06	1829	±51
U08-AM-MBM-10	10	10	3048	±51



TOLERANCE		INCHES		M/M	Tri-Net Technology, Inc. http://www.trinetusa.com				
. X	. 015			. 30	SCALE	NONE		REV	A
. XX	. 010			. 10	UNIT	MM			
. XXX	. 005			. 05	SHEET	1/1			
DRAWN BY					DATE	03/09/05			
CHECK BY					TITLE	USB AM TO MINI USB BM			
APPD BY					PART NO.	U08-AM-MBM-XX			